



Product code:	OL055 (LOW PROFILE VERSION)
Sign size:	48 x 15
Lighting type:	Daylight viewable LEDs
Weight:	5.0 kg
DDA compliant:	Side
Maximum character height:	155mm
Static characters:	1-16
Scrolling text:	1 & 2 lines



Case dimensions: W510mm x H210mm x D50mm
Viewing area: W461mm x H155mm

No	Part No	Product Code	Description	Qty
1	5136-20-01		48*15 LED CASE	1
2	5136-20-02		48*15 LED REAR PANEL	1
3	7655-01-01	PC206	48*15 LED DISPLAY BOARD (AMBER LED)	1
4	7517-01-01	PC081	LED SIGN 3V POWER SUPPLY PCB ASSY	1
5	7518-01-01	PC082	LED SIGN 5V POWER SUPPLY PCB ASSY	1
6	7522-01-01	PC085	AMBIENT LIGHT SENSOR	1
7	0007-05-04		340MM 5 WAY AMP POWER CABLE	1
8	7564-01-01	PC136	LED INTERCONNECT SUPER MOOSE PWR BRD	1
9	7611-01-01	PC161	OUTSIDE LED MK2 SIGN PROCESSOR	1
10	0006-05-03		8W-510MM MOLEX CABLE ASSY	1
11	0001-05-06		14W-410MM MOLEX CABLE ASSY	1

TECHNICAL INFORMATION

Operating voltage	18 – 32 volts DC
Normal operating power consumption (33% LEDs on)	0.3 amps @ 24v DC (7 watts approx)
Max power consumption (all LEDs on full brightness)	0.8 amps @ 24v DC (18 watts approx)
Standard communications	RS 485 – other options available
Temperature range	-20C to + 60C
Storage temperature range	-20C to + 80C
LED pitch	Horizontal - 9.7mm/Vertical - 10.2mm
Humidity (operating)	95% max
Shock	10g max /11ms/3 axes
Vibration	1g/5-100 Hz/3 axes

NB: Power consumption will vary according to the message displayed. Environmental test information is taken from the results obtained from testing products based on a similar design.



Certified Supplier No. 816
ISO 14001:2004

Hanover Displays Ltd, Unit 24, Cliffe Industrial Estate, Lewes,
East Sussex, BN8 6JL.

Tel: +44 (0)1273 477528 Fax: +44 (0)1273 407766

