



<b>Product code:</b>	<b>OL087D+FIT (INTEGRATED CONTROLLER)</b>
Sign size:	96 x 8
Lighting type:	Daylight viewable LEDs (surface mount)
Weight:	1.7 kg
DDA compliant:	-
Maximum character height:	52mm
Static characters:	3 No & 15+ characters
Scrolling text:	1 line



Case dimensions: W600mm x H105mm x D50mm  
Viewing area: W582mm x H52mm

No	Part No	Product Code	Description	Qty
1	5194-20-01		96*8 LED CASE	1
2	5194-20-02		96*8 LED D-FIT REAR COVER	1
3	5194-20-03		96*8 LED SIGN WINDOW	1
4	7694-01-01	PC238	48*8 LED DISPLAY BOARD	1
5	7694-01-02	PC238A	48*8 LED DISPLAY BOARD & PROCESSOR	1
6	5170-01-06		DERIC+ DIN SLOT SLIM (1MB MEM FLASH)	1

TECHNICAL INFORMATION	
Operating voltage	12 – 32 volts DC
Normal operating power consumption (33% LEDs on)	0.59 amps @ 24v DC (14 watts approx)
Max power consumption (all LEDs on full brightness)	0.75 amps @ 24v DC (16 watts approx)
Standard communications	RS 485 – other options available
Temperature range	-20C to + 60C
Storage temperature range	-20C to + 80C
LED pitch	Horizontal - 6.0mm/Vertical - 6.0mm
Humidity (operating)	95% max
Shock	10g max /11ms/3 axes
Vibration	1g/5-100 Hz/3 axes
NB: Power consumption will vary according to the message displayed. Environmental test information is taken from the results obtained from testing products based on a similar design.	



Certified Supplier No. 816  
ISO 14001: 2008

Hanover Displays Ltd, Unit 24, Cliffe Industrial Estate, Lewes,  
East Sussex, BN8 6JL.

Tel: +44 (0)1273 477528 Fax: +44 (0)1273 407766



Certified Supplier No. 816  
ISO 9001: 2008